

# 1 Port USB Serial

## USB to RS-422, RS-485, RS-530 DB25 Serial Interface Adapter

Item # 2102

The 2102 USB serial interface adapter provides a single USB to RS-422, RS-485, or RS-530 serial port for providing USB connectivity to legacy or non-USB compliant devices. SeaLINK serial interface adapters support standard PC data rates up to 921.6K bps to provide you with the horsepower your serial I/O applications require.

Sealevel's SeaCOM USB software drivers and utilities make installation and operation easy using Windows 98SE, ME, 2000, XP and Vista™ operating systems. After installing the software, simply connect the SeaLINK serial interface adapter to your USB port and the device is immediately recognized by the system as a standard COM: port.



### Unique Features

- ▶ Configurable for RS-422, RS-485, or RS-530
- ▶ High speed UART with 128-byte Tx FIFO and 384-byte Rx FIFO
- ▶ Data rates to 921.6K bps
- ▶ Automatic RS-485 enable/disable
- ▶ All modem control signals implemented
- ▶ Hot-swappable
- ▶ Powered by USB connection
- ▶ DB-25M connector
- ▶ Sealevel software supports Windows 98SE/ME/2000/XP/Vista and Linux operating systems
- ▶ 72" USB cable included (Item# CA179)

### Technical Specifications

Number of Ports	1
Communications Chip	USB/UART
Max Data Rate	921.6K bps
Max Data Distance	4000 feet
USB Spec.	1.1 Compliant 2.0 Compatible
Operating Temperature	0 - +70° C
Storage Temperature	-50° - +105° C
Humidity Range	10 - 90% R.H.
Power Requirement	+5V @ 50mA
Dimensions	3.8 (L) x 2.3 (W) x 1.0 (H)

# SEALEVEL

www.sealevel.com