

2 Port USB Serial

USB to RS-422, RS-485 DB9 Serial Interface Adapter

Item # 2202

The 2202 USB serial I/O adapter provides two RS-422 or RS-485 serial ports for USB connectivity to legacy or non-USB compliant devices. The 2202 supports standard PC data rates up to 921K bps.

Sealevel's SeaCOM USB software drivers and utilities make installation and operation easy using Windows 98SE, ME, 2000, XP and Vista™ operating systems. After installing the software, simply connect the 2202 serial interface adapter to your USB port. The device is immediately recognized by the system. Now your non-USB peripherals can have the same connection simplicity and ease of use as USB aware peripherals.



Unique Features

- ▶ Each port individually configurable for RS-422 or RS-485
- ▶ High speed UART with 128-byte Tx FIFO and 384-byte Rx FIFO
- ▶ Data rates to 921.6K bps
- ▶ Automatic RS-485 enable/disable
- ▶ Serial and USB activity LEDs
- ▶ Hot-swappable
- ▶ Powered by USB connection
- ▶ Sealevel software supports Windows 98SE/ME/2000/XP/Vista and Linux operating systems
- ▶ DB-9M connectors
- ▶ 72" USB cable included

Technical Specifications

Number of Ports	2
Communications Chip	USB/UART
Max Data Rate	921.6K bps
Max Data Distance	4000 feet
USB Spec.	1.1 Compliant 2.0 Compatible
Operating Temperature	0 - +70° C
Storage Temperature	-50° - +105° C
Humidity Range	10 - 90% R.H.
Power Requirement	+5V @ 500mA
Dimensions	7.1 (L) x 5.3 (W) x 1.5 (H)

SEALEVEL

www.sealevel.com