

# 4 Port USB Serial

## USB to RS-232 DB9 Serial Interface Adapter

Item # 2401

The 2401 USB serial I/O adapter provides four RS-232 serial ports for USB connectivity to legacy or non-USB compliant devices. Data rates up to 460.8K bps are supported.

Sealevel's SeaCOM USB software drivers and utilities make installation and operation easy using Windows 98SE, ME, 2000, XP and Vista™ operating systems. After installing the software, simply connect the 2401 serial interface adapter to your USB port. The device is immediately recognized by the system. Now your non-USB peripherals can have the same connection simplicity and ease of use as USB aware peripherals.



### Unique Features

- ▶ High speed UART with 128-byte Tx FIFO and 384-byte Rx FIFO
- ▶ Data rates to 460.8K bps
- ▶ All modem control signals implemented
- ▶ Serial and USB activity LEDs
- ▶ Hot-swappable
- ▶ Powered by USB connection
- ▶ Sealevel software supports Windows 98SE/ME/2000/XP/Vista and Linux operating systems
- ▶ DB-9M connectors
- ▶ 72" USB cable included

### Technical Specifications

Number of Ports	4
Communications Chip	USB/UART
Max Data Rate	460.8K bps
Max Data Distance	50 feet
USB Spec.	1.1 Compliant 2.0 Compatible
Operating Temperature	0 - +70° C
Storage Temperature	-50° - +105° C
Humidity Range	10 - 90% R.H.
Dimensions	7.1 (L) x 5.3 (W) x 1.5 (H)

# SEALEVEL

[www.sealevel.com](http://www.sealevel.com)