

# 4 Port USB Serial

## USB to RS-232, RS-422, RS-485 DB9 Serial Interface Adapter

Item # 2403

The 2403 USB serial I/O adapter provides four RS-232, RS-422, or RS-485 serial ports for USB connectivity to legacy or non-USB compliant devices. Each port is individually configurable for RS-232, RS-422, or RS-485.

Sealevel's SeaCOM USB software drivers and utilities make installation and operation easy using Windows 98SE, ME, 2000, XP and Vista™ operating systems. After installing the software, simply connect the 2403 serial interface adapter to your USB port. The device is immediately recognized by the system. Now your non-USB peripherals can have the same connection simplicity and ease of use as USB aware peripherals.

If your application requires RoHS compliance, order the 2403-RoHS.

### Unique Features

- ▶ Each port individually configurable for RS-232, RS-422, or RS-485
- ▶ High speed UART with 128-byte Tx FIFO and 384-byte Rx FIFO
- ▶ Data rates to 921.6K bps
- ▶ Automatic RS-485 enable/disable
- ▶ Serial and USB activity LEDs
- ▶ Hot-swappable
- ▶ Powered by USB connection
- ▶ Sealevel software supports Windows 98SE/ME/2000/XP/Vista and Linux operating systems
- ▶ DB-9M connectors
- ▶ 72" USB cable included



### Technical Specifications

Number of Ports	4
Communications Chip	USB/UART
Max Data Rate	921.6K bps
Max Data Distance	Up to 4000 ft.
USB Spec.	1.1 Compliant 2.0 Compatible
Operating Temperature	0 - +70° C
Storage Temperature	-50° - +105° C
Humidity Range	10 - 90% R.H.
Dimensions	7.1 (L) x 5.3 (W) x 1.5 (H)

# SEALEVEL

www.sealevel.com