

1 Port Ethernet Serial

Ethernet to Isolated RS-232, RS-422, RS-485 Serial Server with Opto-isolated Input and Reed Relay Output

Item # 4103

Sealevel's 4103 Ethernet to serial server is the easiest way to connect a single RS-232, RS-422, or RS-485 serial port to your Ethernet network. The 4103 also includes a Reed relay output and an optically isolated input to allow remote control and monitoring of real world devices. SeaLINK products use industry standard RFC 2217 TCP/IP protocol for maximizing compatibility with the widest range of applications and devices.

Sealevel's SeaLINK software drivers and utilities make installation and operation easy using Windows 98SE, 2000, XP and Vista™ operating systems. After software installation, the 4103's serial ports appear as virtual COM ports to the host machine. Standard serial operating calls are transparently redirected to the 4103, guaranteeing compatibility with legacy serial devices and enabling backward compatibility with existing software. Serial tunneling is also supported, allowing two native serial devices to communicate over a network. Alternatively, raw data socket mode is supported, eliminating the need for a driver.

To simplify installation and configuration, a printed copy of the SeaLINK QuickStart Guide is included with all Ethernet serial server orders.



Technical Specifications

Number of Ports	1
Max Data Rate	230.4K bps
Max Data Distance	4000 feet
Operating Temperature	0 - +70° C
Storage Temperature	-50° - +105° C
Humidity range	10 - 90% R.H.
Power Requirement	9-30 VDC @ 3.25W
Dimensions	4.5 (L) x 4.2 (W) x 1.1 (H)

Unique Features

- ▶ Ethernet 10/100BaseT (autosense)
- ▶ Configurable as RS-232, RS-422, or RS-485
- ▶ Serial port is optically isolated
- ▶ Automatic RS-485 enable/disable
- ▶ Appears as a virtual COM port to host machine
- ▶ Data rates to 230.4K bps
- ▶ Reed relay output: 60VDC @ 500mA max
- ▶ Optically isolated digital input for monitoring +5V to +24V
- ▶ 120V AC adapter included (12VDC 500mA output, Item# TR104)
- ▶ 9-30VDC power input
- ▶ Sealevel software supports Windows 98SE/2000/XP/Vista operating systems

SEALEVEL

www.sealevel.com