

# Seal/O - Ethernet Data Acquisition Modules

## Ethernet Modbus TCP to 16 Form C Relay Outputs

Item # 450E

The Seal/O-450E provides 16 SPDT Form C relays. Connection to the host device is made via Ethernet 10/100BaseT connection. The Seal/O-450E is powered from your 9-30VDC source, or select from a variety of Sealevel power supply options.

Communicate with the Seal/O-450E using industry standard Modbus TCP protocol or use the Sealevel SeaMAX API software libraries from your application program. Sealevel's SeaMAX software drivers and utilities make installation and operation easy using Windows 2000, XP and Vista™ operating systems.

Expand your I/O network with Seal/O N series products. Seal/O modules are available with Reed and Form C relays, optically isolated inputs, TTL interfaces, A/D and D/A functionality. Up to 246 additional expansion modules can be added using convenient pass-through connectors.

### Unique Features

- ▶▶ 10/100BaseT Ethernet Modbus TCP interface
- ▶▶ 16 SPDT Form C relays
- ▶▶ Removable screw terminals simplify field wiring
- ▶▶ Input power via terminal block or modular connector
- ▶▶ DIN rail mount or table mount
- ▶▶ Sealevel software supports Windows 2000/XP/Vista operating systems



### Technical Specifications

Number of I/O	16 Outputs
Power Requirement	9-30 VDC @ 5.3W
Contact Voltage	60VDC Max
Contact Current	2A Max
Contact Operate Time	2ms Max
Contact Bounce Time	7ms Max
Contact Release Time	1ms Max
Operating Temperature	0 - +70° C
Storage Temperature	-50° - +105° C
Humidity Range	10 - 90% R.H.
Dimensions	7.5 (L) x 5.1 (W) x 1.3 (H)

# SEALEVEL

www.sealevel.com