

# USB Digital I/O - SeaDAC

## USB to 16 Form C Relay Outputs Digital Interface Adapter

Item # 8225

The 8225 provides 16 SPDT Form C relays that can be easily controlled from your computer's USB port. Each relay output is rated for switching up to 60VDC @ 2A. The outputs are grouped in four-bit segments that each share a common for easy wiring via removable 3.5mm terminal blocks.

SeaDAC modules are housed in a rugged, attractive plastic enclosure and include a highly-retentive USB Type B connector to prevent accidental disconnection. Standard operating temperature range of SeaDAC modules is 0° C to 70° C and extended temperature range (-40° C to +85° C) is optional.

The SeaMAX software suite supports the SeaDAC family and is designed to work with third party applications via the SeaMAX API. Installation and operation is easy using Windows 2000/XP and SeaMAX now supports the Windows Vista operating system. Download the updated driver below.

### Unique Features

- ▶▶ 16 SPDT Form C relays
- ▶▶ Removable screw terminals simplify field wiring
- ▶▶ High-retention USB Type B connector prevents accidental disconnection of USB cable
- ▶▶ Housed in rugged, attractive plastic enclosure
- ▶▶ Sealevel software supports Windows 2000/XP/Vista operating systems
- ▶▶ 72" USB A to B cable included
- ▶▶ Includes 5V @ 2.4A wall mount power supply (Item# TR101)



### Technical Specifications

Number of I/O	16 Outputs
Power Requirement	+5V @ 500mA
Contact Voltage	60VDC Max
Contact Current	2A Max
Contact Operate Time	2ms Max
Contact Bounce Time	7ms Max
Contact Release Time	1ms Max
Operating Temperature	0 - +70° C
Humidity Range	10 - 90% R.H.
USB Specification	1.1 Compliant 2.0 Compatible
Dimensions	9.2 (L) x 5.3 (W) x 1.7 (H)

# SEALEVEL

www.sealevel.com