

R08L200-OFU1

8.4" Open Frame Display



KEY FEATURES

- 8.4", 800 x 600
- Open frame
- VESA mount
- VGA and HDMI input



SPECIFICATIONS


Display			
Resolution	800x600	Size	8.4 inches
Contrast Ratio	600:1	Panel Brightness	600 nits
Display Color	262K Colors	View Angles	75,75,60,70
Type	Resistive Touch Screen Protection Glass w/o Touch Function(Optional) SAW Touch (Surface Acoustic Wave) (Optional)		
Environment			
Operating Humidity	10% to 90% (non-condensing)	Operating Temperature	0~50°C
Storage Temperature	-10~60°C		
Certification			
Certification	CE, FCC		
IO Ports			
USB Port	1 x USB for Touch Screen	Video	1 x VGA 1 x HDMI(Optional) 1 x DVI (Optional)
Audio	Optional: Audio line in (3.5mm) + 2 x Speaker		
Mechanical			
Dimension	251.2 x 174.8 x 49 mm	Weight	1.4 kg
Mounting	VESA Mount/ Panel Mount	Enclosure	Metal
Cooling System	Fanless Design		
Accessory			
Accessory	1 x VGA cable 1 x HDMI cable 100~240V AC to DC Adapter Power Cord Manual VESA screws(Varies by product) Remote Controller (Optional,Varies by product)		
Power			
Power Rating	12V DC input		
Control			

Button

5 Keys: -, +, Power, Esc, Enter
(with LED Indicators: Power on, Stand by)

DIMENSIONS

UNIT:MM



NOTE

1. This is a simplified drawing and some components are not marked in detail.
2. Please contact our sales representative if you need further product information.
3. All specifications are subject to change without prior notice.
4. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.