



Unit: mm

## Specifications

<b>SoC</b>	DM&P SoC CPU Vortex86DX- 600MHz Real Time Clock with Lithium Battery Backup
<b>Cache</b>	L1:16K I-Cache, 16K D-Cache L2 Cache 128KB
<b>Bus</b>	PC/104 standard compliant PCI-104 (Optional)
<b>BIOS</b>	AMI BIOS
<b>System Memory</b>	128MB DDR2 Onboard
<b>Watchdog Timer 0 &amp; 1 Sets</b>	Software programmable from 30.5μ sec.to 512 sec. x 2 sets (Watchdog 1 fully compatible with M6117D)
<b>VGA</b>	XGI Volari Z9s Chipset VGA and TFT Flat Panel Interface Support Onboard 32MB VGA Memory, support resolution up to 1280x1024, 16M colors
<b>Flash Disk Support</b>	MSTI EmbedDisk Module (16MB and above) 44-pin IDE to Micro SD (Optional)
<b>PWM</b>	16~24 Channels
<b>I/O Interface</b>	Enhanced IDE port (UltraDMA-100/66/33) x1 RS-232 port x1 RS-232/422/485 port x1 USB port (Ver2.0) x2 Parallel port x1 16-bit GPIO port x1
<b>Connectors</b>	2.0mm 44-pin box header for IDE x1 2.0mm 44-pin box header for LCD x1 2.0mm 26-pin box header for Printer x1 2.0mm 20-pin box header for 16-bit GPIO x1 2.0mm 10-pin box header for VGA x1 2.0mm 10-pin box header for USB x1 2.0mm 10-pin box header for RS-232 x2 2.54mm 5-pin box header for Keyboard x1 2.54mm 5-pin header for Mouse x1 2.54mm 3-pin header for RS-485 x1 2.54mm 2-pin header for Reset x1 2.54mm 7-pin header for Redundancy Signal x1 (Optional) 2.54mm 2-pin header for System-Fail-SW x1 (Optional) 1.25mm 6-pin wafer for JTAG x1
<b>Power Requirement</b>	Single Voltage +5V @ 600mA
<b>Weight</b>	80g

**Board Size** 90 x 96mm (3.54 x 3.77 inches)

**Operating Temperature** -20°C ~ +70°C

-40°C ~ +85°C (Optional)

## Packing List

- VDX-6372 x1
- CD for User's Manual & Driver x1
- Cable
  - HDD 44P (2.0) x1
  - PRINT (2.0) x1
  - VGA (2.0) x1
  - RS-232 (2.0) x2
  - USB (2.0) x1
  - GPIO (2.0) x1
  - PS2 KB White x1
  - PS2 Mouse Black x1
- Screw Kit x1

## Ordering information

- **VDX-6372** Vortex86DX PC/104 CPU Module with 128MB DDR2
- **VDX-6372-PLUS** Vortex86DX PC/104+ CPU Module with 128MB DDR2